

Application Serial No. 10/669,913
Reply to Office Action of May 4, 2006

PATENT
Docket: CU-3369

RECEIVED
CENTRAL FAX CENTER

OCT 31 2006

Amendments To The Claims

The listing of claims presented below will replace all prior versions, and listings, of claims in the application.

Listing of claims:

1. (Currently amended) A liquid crystal display device comprising:

an analog voltage signal generator for storing an input synchronous signal and a plurality of input digital data ~~signal~~ signals in response to a write enable signal, and converting the stored digital data ~~signal~~ signals into a plurality of analog voltage signal pairs in response to an output enable signal;

a plurality of reference voltage generators for dividing a boosted source voltage according to the analog voltage signal pairs from the analog voltage signal generator to generate a plurality of reference voltages; and

a source driver ~~integrated~~ circuit for receiving the plurality of reference voltages from the plurality of reference voltage generators,

wherein a digital/analog converter of the analog voltage signal generator changes a reference voltage value and outputs a changed value reference voltage value to the reference voltage generators, ~~thus to thereby change~~ changing a contrast ratio a range of a contrast ratio according to the changed reference voltage values when a command ~~to change~~ changing a reference voltage value is transferred to the digital/analog converter.

Application Serial No. 10/669,913
Reply to Office Action of May 4, 2006

PATENT
Docket: CU-3369

2. (Currently amended) A liquid crystal display device as claimed in claim 1, wherein the analog voltage signal generator includes:

a data storage section for storing the input synchronous signal and the plurality of input digital data signals in response to the write enable signal;

the digital/analog converter for converting the plurality of input digital data signals stored in the data storage section into a plurality of analog signals in response to the input synchronous signal when the output enable signal is generated; and

a buffer amplifier for amplifying the plurality of input analog signals and outputting the plurality of analog voltage signal pairs.

3. (Original) A liquid crystal display device as claimed in claim 2, wherein the data storage section stores a fixed reference voltage signal pair according to voltage-transmission factor curve feature, and the digital/analog converter changes the fixed reference voltage signal pair stored in the storage section in response to an external reference voltage change command and outputs a changed reference voltage.

4. (Original) A liquid crystal display device as claimed in claim 1, wherein the plurality of reference voltage generators include a plurality of resistors connected to each other in series between a power supply terminal and a ground terminal for generating the plurality of reference voltages.